

SPECS SHEET 4PON MINI OLT

| Item | | V1600D-MINI |
|------------------------|--------------------------|--|
| 1000M Uplink Port | QTY | 4 |
| | Copper | 4*10/100/1000M auto-negotiation |
| EPON Port | QTY | 4 |
| | Physical Interface | SFP Slots |
| | Connector Type | 1000BASE-PX20+ |
| | Max splitting ratio | 1:64 |
| Management Ports | | 1*10/100BASE-T out-band port, 1*CONSOLE port |
| PON Port Specification | Transmission Distance | 20KM |
| | EPON port speed | Symmetrical 1.25Gbps |
| | Wavelength | TX 1490nm, RX 1310nm |
| | Connector | SC/PC |
| | Fiber Type | 9/125μm SMF |
| | TX Power | +2~+7dBm |
| | Rx Sensitivity | -27dBm |
| | Saturation Optical Power | -6dBm |
| Management Mode | | SNMP, Telnet and CLI |
| Dimension(L*W*H) | | 225mm*200mm*43.6mm |
| Weight | | 2kg |
| Power Supply | 220VAC | AC:90~264V, 47/63Hz |
| Power Consumption | | 25W |
| Operating Environment | Working Temperature | -10~+55°C |
| | Storage Temperature | -40~+85°C |
| | Relative Humidity | 5~90%(non-conditioning) |